

R22 系列转子压缩机

电源	系列	代表机型	制冷量	能效比	排量	功率	电容	外形尺寸										外形图 代码
Power source	Series	Typical Model	Capacity	COP	Displ	Power	Capacitor	Outside Dimensions										
			W/BTU/H	W/W/BTU/ WH	cm ³ /rev	W	μF/450V· AC	H1	H2	H3	H4	H5	A	B	C	D	α	
220V-240V ~50Hz 1φ	小1HP	QXR-136AT	2250/7680	3.0/10.24	13.6	750	20	294	258	220	43	11	86	50.8	8	9.7	20	A
	1HP	QXR-140HT	2300/7850	3.2/10.92	14	718	25	302	263	220	39	11	92	50.8	8	9.7	20	B
		QXR-148GT	2420/8260	3.2/10.92	14.8	756	30	305	265	220	31.5	21.5	92	50.8	8	9.7	20	B
		QXR-148BT	2420/8260	3.12/10.64	14.8	776	25	302	263	236	39	11	107	75	8	12.8	30	B
		QXR-148HT	2420/8260	3.2/10.92	14.8	756	30	302	263	220	39	11	92	50.8	8	9.7	20	B
		QXR-156HT	2550/8703	3.2/10.92	15.6	797	30	302	263	220	39	11	92	50.8	8	9.7	20	B
		QXR-159GT	2620/8940	3.2/10.92	15.9	818	30	305	265	220	31.5	21.5	92	50.8	8	9.7	20	B
		QXR-159HT	2620/8940	3.2/10.92	15.9	818	30	302	263	220	39	11	92	50.8	8	9.7	20	B
		QXR-16AT	2550/8700	3.0/10.24	15.6	850	30	295	255	220	31.5	21.5	92	50.8	8	9.7	20	B
	QXR-17AT	2745/9400	3.0/10.24	16.5	915	30	295	255	220	31.5	21.5	92	50.8	8	9.7	20	B	
	1.5HP	QXR-188AT	3130/10683	3.05/10.41	18.8	1026	30	310	271	235	39	11	107	75	8	12	30	B
		QXR-196AT	3260/11126	3.05/10.41	19.6	1069	30	310	271	235	39	11	107	75	8	12	30	B
		QXR-203AT	3400/11604	3.05/10.41	20.3	1115	30	301	271	236	39	11	107	75	8	12	30	B
		QXR-207AT	3460/11809	3.05/10.41	20.7	1135	30	301	271	236	39	11	107	75	8	12	30	B
		QXR-210AT	3550/12116	3.12/10.64	21.0	1138	30	314	284	236	39	21.5	107	75	8	12	30	B
		QXR-212AT	3550/12116	3.05/10.41	21.2	1164	30	301	271	236	39	11	107	75	8	12	30	B
		QXR-21ET	3550/12116	3.0/10.24	21.2	1180	30	313	273	236	31.5	21.5	107	75	8	12	30	B
		QXR-189LT	3100/10580	2.95/10.07	18.9	1050	30	313	273	236	31.5	21.5	107	75	8	12	30	B
		QXR-198LT	3260/11126	2.95/10.07	19.8	1105	30	313	273	236	31.5	21.5	107	75	8	12	30	B
		QXR-226BT	3850/13143	2.95/10.07	22.6	1305	30	301	271	246	39	11	95	54	8	9.7	30	B
		QXR-196GT	3290/11230	3.2/10.92	19.6	1028	35	336	280	275	39	21.5	114	75	10	12	30	C
		QXR-202GT	3420/11670	3.2/10.92	20.2	1069	35	336	280	275	39	21.5	114	75	10	12	30	C
		QXR-210GT	3560/12150	3.2/10.92	21	1113	35	336	280	275	39	21.5	114	75	10	12	30	C
	QXR-213GT	3600/12290	3.2/10.92	21.3	1125	35	336	280	275	39	21.5	114	75	10	12	30	C	
	QXR-22AT	3770/12870	3.0/10.24	22.2	1256	35	326	270	275	39	21.5	114	75	10	12	30	C	
	QXR-23AT	3990/13620	3.0/10.24	23.5	1330	35	326	270	275	39	21.5	114	75	10	12	30	C	
	2HP	QXR-277AT	4800/16380	3.1/10.58	27.7	1550	40	336	280	275	39	21.5	114	75	10	12	30	C
		QXR-288LT	4950/16890	3.05/10.41	28.8	1623	40	336	280	275	39	21.5	114	75	10	12.8	30	C
		QXR-292GT	5000/17065	3.2/10.92	29.2	1563	45	337.5	300	302	46	22	120.5	80	9.7	12.8	50	D
		QXR-300GT	5100/17405	3.2/10.92	30.1	1600	50	337.5	300	302	46	22	120.5	80	9.7	12.8	50	D
		QXR-34AT	5700/19450	3.0/10.24	33.6	1900	50	337.5	300	302	46	22	120.5	80	9.7	12.8	50	D
3HP	QXR-47AT	8000/27300	3.1/10.58	47	2580	65	389	352	309	58	21	124.5	80	10.6	16	50	E	